

# FWD 4/6 Cylinder Rules

- **Basic Rules:**

- Any FWD 4 & 6 cylinder with wheelbase less than 108" No full framed cars!
- Car must be clean of all trash, bumper covers, all body molding, lights, and glass must be removed as well.
- You may run shifter, header, aftermarket fuel cells. No oil/trans coolers allowed. (these cannot add strength to car or will be removed)
- Must have valid driver license (if under 18 must have parent's signature)
- Helmet & eye protection are not optional, must be worn at all times while on the track.
- No fuel leaks or you will not run.
- Seatbelt must be intact and worn at all times on the track.
- Judges decisions are final.
- No alcohol or profanity or you will be disqualified.

- **Cage:**

- 4 point cage is recommended.
- Door bars are to be no more than 10" past door post.
- You can run tank protector. No more than 24" wide. It can go to package tray but cannot be welded or bolted to anything.
- Door bars are to be no bigger than 2"x 6" tubing. Door/seat bar no bigger than 3"x 3" tubing. Tank protector is to be no bigger than 3"x 3" tubing.
- Cage must be at least 5" away from floors pan or anything to strength car other than tank protector to package tray. (No down bars or kickers)
- You may run 3"x 3" center bar for mounting shifter. This cannot strengthen car in anyway.
- Roll over bar no bigger than 2"x 6" tubing must be straight up, can be mounted to roof with 2- ½ inch bolts. Go through roof only with these or they will be removed.